

**WHAT IS CLAIMED IS:**

1. A method comprising;  
obtaining a base signal including a plurality of signal components;  
performing a pyramidal decomposition of the base signal to generate a first decomposed signal;  
increasing the ratio of a desired signal component of the first decomposed signal to other signal components of the first decomposed signal to generate a first modified signal; and  
recomposing the first modified signal to generate an improved base signal.
2. The method as in Claim 1, wherein increasing the ratio includes increasing the desired signal component.
3. The method as in Claim 2, wherein increasing the desired signal component is performed by guiding a sheep artifact with a shepherd artifact.
4. The method as in Claim 1, wherein increasing the ratio includes filtering the other signal components
5. The method as in Claim 4, wherein filtering is includes using a match blur.
6. The method as in Claim 4, wherein filtering includes streak removal.
7. The method as in Claim 1, further including:  
performing a pyramidal decomposition of the first modified signal to generate a second decomposed signal;  
increasing the ratio of a desired signal component of the second decomposed signal to other signal components of the second decomposed signal to

PATENT APPLICATION

6 generate a second modified signal; and  
7 recomposing the modified second decomposed signal to generate a first  
8 recomposed signal.

1 8. The method as in Claim 7, further including:  
2 combining the first recomposed signal with the second modified signal to  
3 generate a first improved signal.

1 9. The method as in Claim 7, further including:  
2 combining the first recomposed signal with the second decomposed signal to  
3 generate a first improved signal.

1 10. The method as in Claim 1, wherein said base signal is a digital representation  
of an analog signal.

11. A method comprising;  
obtaining a digital base image, the base image including a plurality of image components;  
performing a first pyramidal decomposition of the base image to generate a first decomposed image;  
increasing the ratio of a desired image component of the first decomposed image to other image components of the first decomposed image to generate a first modified image;  
performing a pyramidal decomposition of the first modified image to generate a second decomposed image;  
increasing the ratio of a desired image component of the second decomposed image to other image components of the second decomposed image to generate a second modified image;  
recomposing the second modified image to generate a first recomposed image;  
combining the first recomposed image with the first modified image to generate an improved first image;  
recomposing the improved first image to generate an improved base image.

12. The method as in Claim 11, wherein increasing the ratio includes increasing the desired image component.

13. The method as in Claim 12, wherein increasing the desired image component is performed by guiding a sheep artifact with a shepherd artifact.

14. The method as in Claim 11, wherein increasing the ratio includes filtering the other image components

15. The method as in Claim 14, wherein filtering is includes using a match blur.

PATENT APPLICATION

16. The method as in Claim 15, wherein filtering includes streak removal.

PATENT APPLICATION

- 1 17. A digital film development system comprising:  
2 a film processing system, said film processing system including an image  
3 capturing station capable of obtaining sets of data representing an  
4 image formed in film ; and  
5 a data processing system, said data processing system including:  
6 a processor;  
7 memory operably coupled to said processor; and  
8 a program of instructions capable of being stored in said memory and  
9 executed by said processor, said program of instructions  
10 including instructions for:  
11 obtaining a base signal including a plurality of signal  
12 components;  
13 performing a pyramidal decomposition of the base signal to  
14 generate a first decomposed signal;  
15 increasing the ratio of a desired signal component of the first  
16 decomposed signal to other signal components of the  
17 first decomposed signal to generate a first modified  
18 signal; and  
19 recomposing the first modified signal to generate an improved  
20 base signal.
- 1 18. The method as in Claim 17, wherein increasing the ratio includes increasing  
2 the desired signal component.
- 1 19. The method as in Claim 18, wherein increasing the desired signal component  
2 is performed by guiding a sheep artifact with a shepherd artifact.
- 1 20. The method as in Claim 17, wherein increasing the ratio includes filtering the  
2 other signal components

PATENT APPLICATION

- 1 21. The method as in Claim 20, wherein filtering includes using a match blur.
- 1 22. The method as in Claim 20, wherein filtering includes streak removal.
- 2 23. The method as in Claim 17, further including:  
3 performing a pyramidal decomposition of the first modified signal to generate  
4 a second decomposed signal;  
5 increasing the ratio of a desired signal component of the second decomposed  
6 signal to other signal components of the second decomposed signal to  
7 generate a second modified signal; and  
8 recomposing the modified second decomposed signal to generate an improved  
9 first decompose a first recomposed signal.
- 1 24. The method as in Claim 23, further including:  
2 combining the first recomposed signal with the second modified signal to  
3 generate a first improved signal.
- 1 25. The method as in Claim 23, further including:  
2 combining the first recomposed signal with the second decomposed signal to  
3 generate a first improved signal.
- 1 26. The method as in Claim 1, wherein said base signal is a digital representation  
2 of an analog signal.

PATENT APPLICATION

1 27. A digital image tangibly embodied in a computer readable medium, said  
2 digital image generated according to a method comprising:  
3 obtaining a digital base image, the base image including a plurality of  
4 image components;  
5 performing a first pyramidal decomposition of the base image to  
6 generate a first decomposed image;  
7 increasing the ratio of a desired image component of the first  
8 decomposed image to other image components of the first  
9 decomposed image to generate a first modified image;  
10 performing a pyramidal decomposition of the first modified image to  
11 generate a second decomposed image;  
12 increasing the ratio of a desired image component of the second  
13 decomposed image to other image components of the second  
14 decomposed image to generate a second modified image;  
15 recomposing the second modified image to generate an improved first  
16 first recomposed image;  
17 combining the first recomposed image with the first modified image to  
18 generate an improved first image;  
19 recomposing the improved first image to generate an improved base  
20 image.

1 28. The digital image as in Claim 27, wherein increasing the ratio includes  
2 increasing the desired image component.

1 29. The digital image as in Claim 28, wherein increasing the desired image  
2 component is performed by guiding a sheep artifact with a shepherd artifact.

1 30. The digital image as in Claim 28, wherein increasing the ratio includes  
2 filtering the other image components

PATENT APPLICATION

- 1 31. The digital image as in Claim 30, wherein filtering is includes using a match  
2 blur.
- 1 32. The digital image as in Claim 30, wherein filtering includes streak removal.